


Pneumatic Tacker

Type 72/14-452 A

The ideal tacker for industrial purpose. Gives best performance wherever quick and durable fastening is required. The cycle speed can be infinitely varied between 0 – 1600 staples per minute. Without adjustment an exact stapling can be achieved even at highest operation speed, thus optimizing the staple consumption and reducing time requirement. Where higher staple capacity is required the long magazine version reduces the reloading frequency by half.



Popular applications:

Upholstery, office swivel chairs, chairs

	<u>Automatic</u>	<u>Automatic Long</u>
Length:	201 mm	327 mm
Width:	40 mm	40 mm
Height:	149 mm	149 mm

Technical data

Type description:	72/14-452 A Automatic valve	72/14-452 AL Automatic valve / long magazine
Article code:	12000079	12000080
Magazine type :	Bottom loader	Bottom loader
Safety:	-	-
Fastener type:	Type 72	Type 72
Magazine capacity:	194	377
Fasteners per strip:	1 x 182	2 x 182
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Trigger frequency:	0 – 1600 per min.	0 – 1600 per min.
Air consumption/operation:	0.3 litre / 6 bar	0.3 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 77 dB	L pA, 1s, d= 77 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB	L WA, 1 s,d= 87 dB
Weight:	1.16kg	1.34 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, allen keys SW 8, SW 13, silencer.

Subject to technical modifications.

Accessories:

Articel code	Description
14400827	Adjustable roller edge guide (assembly in factory)
14400838	Adjustable roller edge guide (assembly in factory)
14400862	Roller edge guide, resilient (assembly in factory)
14400676	Cap

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Product leaflet 452 A

Pneumatic Tacker Type 72/14-452 A

Staples type 72



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
72/06 NK Hard	6
72/08 NK Hard	8
72/10 NK Hard	10
72/12 NK Hard	12
72/14 NK Hard	14

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut