

Pneumatic Tacker Type 97/25-550

The BeA 97/25-550 is a light and powerful tool, that drives type 97 staples in length from 10 to 25 mm. The bottom loading magazine allows for quick and easy reloading, the long slender nose allows fastening even in hard to reach areas and provides better visibility for more precise fastener placement.



Popular applications:

Corner blocks, drawer runners, picture framing, lattice panels, carpeting, case backs

Length:	203 mm
Width:	47 mm
Height:	178 mm

Technical data

Type description:	97/25-550 Standard	97/25-550 Single
Article code:	12000156	12000363
Magazine type :	Bottom loader	Bottom loader
Safety:	-	Single actuation
Fastener type:	Type 97	Type 97
Magazine capacity:	156	156
Fasteners per strip:	1 x 100	1 x 100
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Air consumption/operation:	0,45 litre / 6 bar	0,45 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 80 dB	L pA, 1s, d= 80 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 88 dB	L WA, 1 s,d= 88 dB
Weight:	1,21 kg	1,21 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code

14400827
14405489
14405569
14405571

Description

Adjustable roller edge guide (assembly in factory)
Adjustable roller edge guide (assembly in factory)
Remote Valve
Mounting flange

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Pneumatic Tacker Type 97/25-550

Staples type 97



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
97/10 NK HZ	10
97/12 NK HZ	12
97/14 NK HZ	14
97/16 NK HZ	16
97/19 NK HZ	19
97/22 NK HZ	22
97/25 NK HZ	25

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut