

Pneumatic Stapler

Type 71/16-421 25 mm Nose

The light but powerful stapler of the 420 series takes staples type 71 in leg lengths from 6 mm to 16 mm. The low air consumption, long service life and ease of maintenance of this stapler make it a real cost saver. The bottom loading magazine allows easy and quick loading. Further features are the ergonomic design and the integrated silencer. This is a versatile tool for industry and the craftsman.



Popular applications:

Upholstered furniture, chairs, TV and stereo cabinets, loudspeakers, wicker and rattan furniture, perambulators, automobile industry

Length: 221 mm
Width: 43 mm
Height: 144 mm

Technical data

| | | |
|---|--|-----------------------|
| Type description: | 71/16-421 25 mm Nose Standard / Contact | 71/16-421 Profile |
| Article code: | 12000330 / 12000348 | 12000324 |
| Magazine type : | Bottom loader / Bottom loader | Bottom loader |
| Safety: | - / Contact actuation | - |
| Fastener type: | Type 71 / Type 71 | Type 71 |
| Magazine capacity: | 190 / 190 | 190 |
| Fasteners per strip: | 1 x 182 / 1 x 182 | 1 x 182 |
| Operating pressure: | 5 – 6 bar / 5 – 6 bar | 5 – 6 bar |
| Max. operating pressure: | 6 bar / 6 bar | 6 bar |
| Air consumption/operation: | 0,3 litre / 6 bar / 0,3 litre / 6 bar | 0,3 litre / 6 bar |
| Inner hose diameter: | Ø 9 mm LW recommended | Ø 9 mm LW recommended |
| Emission sound pressure level at the workstation: | L pA, 1s, d= 79 dB | L pA, 1s, d= 79 dB |
| Single-shot emission sound pressure level: | L WA, 1 s,d= 87 dB | L WA, 1 s,d= 87 dB |
| Weight: | 0.94 kg / 1,9 kg | 0.97 kg |

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.
For safety reasons we recommend the BeA single release if working pressure allows this.

Accessories:

Subject to technical modifications.

| Article code | Description |
|--------------|--|
| 14400827 | Adjustable roller edge guide, long (assembly in factory) |
| 14400838 | Adjustable roller edge guide (assembly in factory) |
| 14405948 | Back nose assembly set 6mm |
| 14405424 | Cap, Alu |
| 14403330 | Remote valve, complete |
| 14400862 | Roller edge guide, resilient (assembly in factory) |
| 14405158 | Guide plate for sinned nose |

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type 71/16-421 25 mm Nose



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0)4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG

Staples type 71



| Description | L = Length mm |
|-------------|------------------|
| 71/06 NK | 6 |
| 71/08 NK | 8 |
| 71/10 NK | 10 |
| 71/12 NK | 12 |
| 71/14 NK | 14 |
| 71/16 NK | 16 |

Other lengths and finishes are also available on request.

Explanations:

| | | | |
|------------------------------------|--------------------------------|--|----------------------|
| NK = galvanized steel | BK = bright steel | LM = aluminium | HZ = resin coated |
| NKS = galvanized steel, extra hard | BKS = bright steel, extra hard | NR = stainless steel, material. 1.4401 | DP = divergent point |
| NKH = galvanized steel, hard | MS = brass | RF = rust resistant, material 1.4301 | SA = step cut |