

Pneumatic Tacker

Type 90/25-552

The BeA 90/25-552 is a light and powerful tool, that drives type 90 staples in length from 10 to 25 mm. The bottom loading magazine allows for quick and easy reloading, the long slender nose allows fastening even in hard to reach areas and provides better visibility for more precise fastener placement.

The cycle speed of the automatic version can be infinitely varied between 0 – 900 staples per minute. Without adjustment an exact stapling can be achieved even at highest operation speed, thus optimizing the staple consumption and reducing time requirement.



Popular applications:

Cabinetry, trim & moldings, shutter louvers, lattice panels, picture frames.

Length:	203 mm
Width:	47 mm
Height:	178 mm

Technical data

Type description:	90/25-552 Standard / Single	90/25-550 A Automatic
Article code:	12000158 / 12000293	12000395
Magazine type :	Bottom loader	Bottom loader
Safety:	- / Single actuation	-
Fastener type:	Type 90	Type 90
Magazine capacity:	111	111
Fasteners per strip:	1 x 100	1 x 100
Operating pressure:	5 – 6 bar	5 – 6 bar
Max. operating pressure:	6 bar	6 bar
Air consumption/operation:	0,45 litre / 6 bar	0,45 litre / 6 bar
Trigger frequency:	-	0 – 900 per min.
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 80 dB	L pA, 1s, d= 80 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 88 dB	L WA, 1 s,d= 88 dB
Weight:	1,21 kg	1,21 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer. For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14400827	Adjustable roller edge guide (assembly in factory)
14405489	Adjustable roller edge guide (assembly in factory)
14405569	Remote Valve
14405571	Mounting flange

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Pneumatic Tacker Type 90/25-552

Staples type 90



BeA Deutschland
Befestigungstechnik GmbH
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
90/12 NK HZ	12
90/15 NK HZ	15
90/18 NK HZ	18
90/21 NK HZ	21
90/25 NK HZ	25

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut