

T-Nailer Type T 54-155

A lightweight tool with compact design for driving T-nails, in shank lengths from 25 to 50mm. The ideal tool for packaging and the production of crates, pallets, banding, etc. For fastening metal sheets and aluminum mouldings as well as applications in truck and trailer construction.



Popular applications:

Boxes, cases, crates, pallets, packaging, form work, truck and trailer construction.

Length: 295 mm
Width: 70 mm
Height: 248 mm

Technical data

Type description:	T 54-155 Standard
Article code:	12000243
Magazine type :	Top loader
Safety	Contact actuation
Fastener type:	Type T
Magazine capacity:	66
Nails per coil:	2 x 33
Operating pressure:	6 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	1.5 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 79 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 87 dB
Weight:	2.7 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 4 m/s²

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Article code	Description
14403409	Remote valve with safety yoke
14403402	Remote valve
14403442	Mounting flange, complete
14400891	High adjustable stop
14406201	Single actuation set
14406959	Grip elongation

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


T-Nailer Type T 54-155

Nails Type T



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
T 25 NK	25
T 32 NK	32
T 38 NK	38
T 44 NK	44
T 50 NK	50

Other lengths and finishes are also available on request.



Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut