

Pneumatic Stapler Type 92/40-722

The BeA 92/40-722 is a compact but powerful tool, that drives staples type 92 from 18 to 40mm. The tool has the power to drive longer length staples type 92 in problematic, harder to penetrate materials. The tool is so powerful, that staples will countersink even into hardwood.



Popular applications:

Case assembly, door and window manufacturing, siding, case backs, trim work.

Length: 343 mm
Width: 70 mm
Height: 228 mm

Technical data

Type description:	92/40-722	92/40-722
Contact	Contact	Single
Article code:	12000343	12000409
Magazine type :	Top loader	Top loader
Safety:	Contact actuation	Single actuation
Fastener type:	Type 92	Type 92
Magazine capacity:	211	211
Fasteners per strip:	2 x 100	2 x 100
Operating pressure:	5 – 8 bar	5 – 8 bar
Max. operating pressure:	8 bar	8 bar
Air consumption/operation:	1,0 litre / 6 bar	1,0 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 83 dB	L pA, 1s, d= 83 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 89 dB	L WA, 1 s,d= 89 dB
Weight:	2,1 kg	2,1 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is 4,1 m/s²

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

Accessories:

Article code	Description
14406199	Single actuation set
14403421	Remote valve
14403536	Mounting flange
14400992	Attachment for board with with smooth edges
14400921	Guide plate with high-adjustable stop
14400887	Spring-clip attachment
14400888	Rapid-Clip attachment

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type 92/40-722

Staples type 92



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: +49 (0) 4102 78-0
Fax: +49 (0) 4102 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
92/18 NK HZ	18
92/21 NK HZ	21
92/25 NK HZ	25
92/28 NK HZ	28
92/30 NK HZ	30
92/32 NK HZ	32
92/35 NK HZ	35
92/38 NK HZ	38
92/40 NK HZ	40

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut