

Pneumatic Stapler Type 92/32-632 C

The compact and well-balanced BeA Stapler 92/32-632 C is a powerful tool that produces very low noise levels. The stapler takes staples type 92 in leg length from 15 mm to 32 mm. The slender nose affords better operator visibility for more precise fastener placement. This tool has a quick release nose. Its main applications are door and window manufacturing and case goods assembly.



Popular applications:

Case goods, door and window manufacturing, building siding, case backs.

Length:	255 mm
Width:	56,5 mm
Height:	198 mm

Technical data

Type description:	92/32-632 C Contact
Article code:	12000437
Magazine type :	Top loader
Safety:	Contact actuation
Fastener type:	Type 92
Magazine capacity:	125
Fasteners per strip:	1 x 100
Operating pressure:	5 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0.9 litres / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d = 79B
Single-shot emission sound pressure level:	L WA, 1 s,d = 87dB
Weight:	1.37 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the stapler:

Operating instructions, spare parts list, service instructions, silencer.
For safety reasons we recommend the BeA single release if working pressure allows this.

Subject to technical modifications.

Accessories:

Articel code	Description
14400859	Roller edge guide, resilient
14400902	Guide plate with high-adjustable stop
14401076	Single actuation set
14403428	Remote valve
14403527	Mounting flange
14406951	Grip elongation

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type 92/32-632 C



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG

Staples type 92



Description	L = Length mm
92/15 NK HZ	15
92/18 NK HZ	18
92/21 NK HZ	21
92/25 NK HZ	25
92/30 NK HZ	30
92/32 NK HZ	32

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut