

## Pneumatic Pinner Type S 125-569

The compact lightweight BeA pneumatic pinner drives headless pins Ø 1.1 mm in the lengths of 14 – 25 mm. A tool for multitude of uses in the woodworking industry and other applications where headless pins are required. The tool is precision made with a long service life.



### Popular applications:

Interior moulding, panels, furniture industry, picture frames, caravan assembling and associated trades.

Length: 207 mm  
Width: 47 mm  
Height: 180 mm

### Technical data

|   |                              |
|---|------------------------------|
| Type description:                                 | <b>S 125-569</b><br>Standard |
| Article code:                                     | 12000439                     |
| Magazine type :                                   | Side loader                  |
| Safety:   | -                            |
| Fastener type:                                    | Pins Type S 100              |
| Magazine capacity:                                | 126                          |
| Fasteners per strip:                              | 2 x 50                       |
| Operating pressure:                               | 5 – 6 bar                    |
| Max. operating pressure:                          | 6 bar                        |
| Air consumption/operation:                        | 0.45 litre / 6 bar           |
| Inner hose diameter:                              | Ø 9 mm LW recommended        |
| Emission sound pressure level at the workstation: | L pA, 1s, d= 80 dB           |
| Single-shot emission sound pressure level:        | L WA, 1 s,d= 88 dB           |
| Weight:   | 1.06 kg                      |

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

### Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

### Accessories:

| Articel code | Description     |
|--------------|-----------------|
| 14405569     | Remote valve    |
| 14405571     | Mounting flange |

All BeA pneumatic tools can be jig-mounted  
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive  
for Machinery (89/392 EWG)


## Pneumatic Pinner Type S 125-569

### Pins type S 100



BeA Deutschland  
Befestigungstechnik  
P.O.Box 14 80  
D-22904 Ahrensburg  
Phone: (04102) 78-0  
Fax: (04102) 78-250  
www.bea-group.com  
e-mail: [info@bea-group.com](mailto:info@bea-group.com)

a division of  
Joh. Friedrich Behrens AG



| Description | L = Length<br>mm |
|-------------|------------------|
| S 114 NK    | 14               |
| S 116 NK    | 16               |
| S 119 NK    | 19               |
| S 122 NK    | 22               |
| S 125 NK    | 25               |

#### Explanations:

|                                    |                                |  |                      |
|------------------------------------|--------------------------------|--|----------------------|
| NK = galvanized steel              | BK = bright steel              | LM = aluminium                         | HZ = resin coated    |
| NKS = galvanized steel, extra hard | BKS = bright steel, extra hard | NR = stainless steel, material. 1.4401 | DP = divergent point |
| NKH = galvanized steel, hard       | MS = brass                     | RF = rust resistant, material 1.4301   | SA = step cut        |