

Pneumatic Bradder Type SK 350-224CB

The light weight bradder (1,24 kg) drives brad nails type SK 300 in the length from 18–50 mm. The slim nose and rear-cut magazine allows reaching tight spots. The bradder is equipped with a quick release nose and an adjustable exhaust deflector. The ergonomic design and the rubber grip make the tool operator friendly.



Popular applications:

Attachment of decorative sealing strips, ornaments, rosettes, glazing strips, trim, moulding, chair rails...

Length: 248 mm
Width: 59 mm
Height: 233 mm

Technical data

Type description:	SK 350-224CB
Article code:	12000467
Magazine type :	Side loader
Fastener type:	Brads Type SK 300
Magazine capacity:	104
Fasteners per strip:	2 x 50
Operating pressure:	5 – 8 bar
Max. operating pressure:	8 bar
Air consumption/operation:	0.9 litre / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 73 dB
Single-shot emission sound pressure level:	L WA, 1 s,d= 82 dB
Weight:	1.24 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer: Operating instructions, spare parts list, service instructions, silencer.

Subject to technical modifications.

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.




This tool conforms to the EG Directive
for Machinery (89/392 EWG)

Pneumatic Tacker Type SK 350-224CB

Brads type SK 300



BeA Deutschland
Befestigungstechnik
A division of the
Joh. Friedrich Behrens AG
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com



Description	L = Length mm
SK 318 NK	18
SK 320 NK	20
SK 325 NK	25
SK 330 NK	30
SK 335 NK	35
SK 340 NK	40
SK 345 NK	45
SK 350 NK	50

Form 6.224CB.02.0305

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut